



Round Grab RG-SAFELOCK

The clamping force of the claws is maintained fully in all cases, even if the carrier is operated incorrectly.

- Gripping and laying concrete pipes.
- Patented safety locking system: When lifting the product, the grab generates tension on the pipe, which is maintained even when the product is set down.
- One-man operation.
- With adjustable height supports, which can be adjusted with a scale using the external pipe diameter. This guarantees an optimum grab position.
- Slim design allows joint-sleeve pipes lying close together to be picked up onto the lorry loading area and used in very narrow trenches.
- With handles to guide the claw.
- The eye runs in a setting with 2 hanging positions. One is used for locked grabbing, the other for releasing the catch and for empty lifting. This allows operation with only one person.



RG-20/85-SAFELOCK



RG-75/125-SAFELOCK



RG-100/150-SAFELOCK

RG-20/85-SAFELOCK: Increased grip width and increased working load limit as with RG-20/80.

Besides concrete pipes, **stoneware pipes can also be laid.**

Easy adjustment of the outer diameter by means of a scale and a central lock pin.

Rubber grippers.

Plastic-coated height adjustment bracket.

Durable surface protection by galvanizing.

RG-75/125-SAFELOCK: Easy, continuous adjustment of the external diameter by means of a scale using threaded spindles. Crank included in the delivery.

Replaceable steel grab clamps with a reliable grip.

Optionally available: rubber gripper jaws to prevent surface damage.

Durable surface protection by galvanizing.

RG-100/150-SAFELOCK: Easy, continuous adjustment of the external diameter by means of a scale using threaded spindles. Crank included in the delivery.

Replaceable steel grab clamps with a reliable grip.

Type	Length of Gripper mm (in)	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
RG-20/85-SAFELOCK	420 (16.54)	175 (386)	200 – 870 (7.87 – 34.25)	2,500 (5,512)	54500009
RG-75/125-SAFELOCK	440 (17.32)	370 (816)	720 – 1,280 (28.35 – 50.39)	4,000 (8,818)	54500005
RG-100/150-SAFELOCK	460 (18.11)	535 (1,179)	970 – 1,530 (38.19 – 60.24)	6,000 (13,228)	54500008