Paver Laying and Transportation





Accessories for Hydraulic Installation Clamp HVZ

Adapter

For some installation units it can be advantageous or even necessary, predominantly for the side grippers, to use a special adapter in order to achieve optimal gripping.

The shifting adapter is used with rectangular stones, for instance, to shift pavers into the running bond. (Please, indicate stone formation).

When laying installation units in the herring-bone pattern, it is better not to bother with the half stones on the sides and to use a herring-bone adapter FA instead (Please, indicate stone formation). Special adapters SA for installation units 21-24 or similar are available on request (please, indicate stone formation).

FA for HVZ-UNI

Туре	Description	Dead Weight kg (lbs)	Order-Number
C-Profiles	50 x 30 x 950 mm (2 x 1 x 38 inch) B x H x L	6 (13)	34010018
C-Profiles	50 x 30 x 860 mm (2 x 1 x 34 inch) B x H x L	5.5 (12)	34010046
FA-Adapter for HVZ-UNI	(external bow not required)	10 (22)	41400277
FA-Adapter for HVZ-UNI-II/HVZ-ECO	(for rectangular pavers)	18 (40)	41400847
FA-Adapter for HVZ-UNI-II/HVZ-ECO	(for Uni pavers)	15 (33)	41401042
HD connection hose	600 mm (24 inch) long for hydraulic rotator Indexator 12 L	0.28 (0.62)	22000081
HD connection hose	1,100 mm (44 inch) long for hydraulic rotator HVZ 10 L	0.78 (1.72)	22000032
HD connection hose	1,700 mm (67 inch) long — HVZ 12 L	0.9 (1.98)	22000007
HD connection hose	2,500 mm (10 inch) long — HVZ/VZ-HS 12 L	1.1 (2.43)	22000014
HD connection hose	3,000 mm (10 inch) long — HVZ 12 L	1.7 (3.75)	22000312